



	Specification Options
Description	Track accessory with magnetic instalment.
Light Source	LED
Power Consumption	4W
Luminous Flux	Dependant on luminaire package
Colour	2700K – 6500K
Beam Angle	12°, 34° or 48°
CRI	80
Lifetime	50,000 Hours
Finish	Sandy black or white
Ingress Protection	IP20
Diffuser	N/A
Dimming/Control	Non dimmable or dimmable
Dimensions	L: 84mm W: 34mm D: 181mm



	Specification Options
Description	Track accessory with magnetic instalment.
Light Source	LED
Power Consumption	8W
Luminous Flux	Dependant on luminaire package
Colour	2700K – 6500K
Beam Angle	12°, 34° or 48°
CRI	80
Lifetime	50,000 Hours
Finish	Sandy black or white
Ingress Protection	IP20
Diffuser	N/A
Dimming/Control	Non dimmable or dimmable
Dimensions	L: 163.5mm W: 34mm D: 181mm



	Specification Options
Description	Track accessory with magnetic instalment.
Light Source	LED
Power Consumption	16W
Luminous Flux	Dependant on luminaire package
Colour	2700K – 6500K
Beam Angle	12°, 34° or 48°
CRI	80
Lifetime	50,000 Hours
Finish	Sandy black or white
Ingress Protection	IP20
Diffuser	N/A
Dimming/Control	Non dimmable or dimmable
Dimensions	L: 322.5mm W: 34mm D: 181mm



	Specification Options
Description	Track accessory with magnetic instalment.
Light Source	LED
Power Consumption	8W
Luminous Flux	Dependant on luminaire package
Colour	2700K – 6500K
Beam Angle	12°, 34° or 48°
CRI	80
Lifetime	50,000 Hours
Finish	Sandy black or white
Ingress Protection	IP20
Diffuser	N/A
Dimming/Control	Non dimmable or dimmable
Dimensions	L: 163.5mm W: 34mm D: 181mm



	Specification Options
Description	Track accessory with magnetic instalment.
Light Source	LED
Power Consumption	16W
Luminous Flux	Dependant on luminaire package
Colour	2700K – 6500K
Beam Angle	12°, 34° or 48°
CRI	80
Lifetime	50,000 Hours
Finish	Sandy black or white
Ingress Protection	IP20
Diffuser	N/A
Dimming/Control	Non dimmable or dimmable
Dimensions	L: 322mm W: 34mm D: 55.5mm



	Specification Options
Description	Track accessory with magnetic instalment.
Light Source	LED
Power Consumption	8W
Luminous Flux	Dependant on luminaire package
Colour	2700K – 6500K
Beam Angle	12°, 34° or 48°
CRI	80
Lifetime	50,000 Hours
Finish	Sandy black or white
Ingress Protection	IP20
Diffuser	N/A
Dimming/Control	Non dimmable or dimmable
Dimensions	L: 163mm W: 34mm D: 55.5mm